K models (K48/K61) 6-cylinder

K 1600 GT, K48		Model code: 0601			
	Tyre type, front	Size, front	Tyre type, rear	Size, rear	Comment
	Metzeler				
	Roadtec Z8 Interact	120/70 ZR17 M/C (58W) TL	Roadtec Z8 Interact C	190/55 ZR17 M/C (75W)	
K 1600 GT, K48 (USA)		Model code: 0611			
	Tyre type, front	Size, front	Tyre type, rear	Size, rear	Comment
	Metzeler				
	Roadtec Z8 Interact	120/70 ZR17 M/C (58W) TL	Roadtec Z8 Interact C	190/55 ZR17 M/C (75W)	
K 1600 GT, K48 11		Model code: 0F01			
	Tyre type, front	Size, front	Tyre type, rear	Size, rear	Comment

Dilugestone	Brid	lgestone
-------------	------	----------

Metzeler

BT 022F F	120/70 ZR17 M/C (58W)	BT 021R F	190/55 ZR17 M/C (75W)
T30F L	120/70 ZR17 M/C (58W) TL	T30F L	190/55 ZR17 M/C (75W)
Metzeler			
Roadtec 01 HWM	120/70 ZR17 M/C (58W) TL	Roadtec 01 HWM	190/55 ZR17 M/C (75W)

K 1600 GT, K48 11 (USA)		Model code: 0F11			
	Tyre type, front	Size, front	Tyre type, rear	Size, rear	Comment
	Bridgestone				
	BT 022F F	120/70 ZR17 M/C (58W)	BT 021R F	190/55 ZR17 M/C (75W)	
	T30F L	120/70 ZR17 M/C (58W) TL	T30F L	190/55 ZR17 M/C (75W)	

	Roadtec 01 HWM	120/70 ZR17 M/C (58W) TL	Roadtec 01 HWM	190/55 ZR17 M/C (75W)	
K 1600 GTL, K48		Model code: 0602			
	Tyre type, front	Size, front	Tyre type, rear	Size, rear	Comment
	Metzeler				
	Roadtec Z8 Interact	120/70 ZR17 M/C (58W) TL	Roadtec Z8 Interact C	190/55 ZR17 M/C (75W)	
K 1600 GTL, K48 (USA)		Model code: 0612			
	Tyre type, front	Size, front	Tyre type, rear	Size, rear	Comment
	Metzeler				

Size, front

120/70 ZR17 M/C (58W) TL Roadtec Z8 Interact C

Tyre type, rear

190/55 ZR17 M/C (75W)

Comment

Size, rear

Roadtec Z8 Interact

Tyre type, front

Rrid	σρετοηρ
DITU	gestone
	0

BT 022F F	120/70 ZR17 M/C (58W)	BT 021R F	190/55 ZR17 M/C (75W)
T30F L	120/70 ZR17 M/C (58W) TL	T30F L	190/55 ZR17 M/C (75W)
Metzeler			
Roadtec 01 HWM	120/70 ZR17 M/C (58W) TL	Roadtec 01 HWM	190/55 ZR17 M/C (75W)

K 1600 GTL, K48 12 (USA)		Model code: 0F12			
	Tyre type, front	Size, front	Tyre type, rear	Size, rear	Comment
	Bridgestone				
	BT 022F F	120/70 ZR17 M/C (58W)	BT 021R F	190/55 ZR17 M/C (75W)	
	T30F L	120/70 ZR17 M/C (58W) TL	T30F L	190/55 ZR17 M/C (75W)	
	Metzeler				
	Roadtec 01 HWM	120/70 ZR17 M/C (58W) TL	Roadtec 01 HWM	190/55 ZR17 M/C (75W)	

KACOO CTI Frankriina KAO					
K 1600 GTL Exclusive, K48		Model code: 0603			
	Tyre type, front	Size, front	Tyre type, rear	Size, rear	Comment
	NA de la la co				
	Metzeler				
	Roadtec Z8 Interact	120/70 ZR17 M/C (58W) TL	Roadtec Z8 Interact C	190/55 ZR17 M/C (75W)	
K 1600 GTL Exclusive, K48 (USA)		Model code: 0613			
, , , , , , , , , , , , , , , , , , , ,				1	
	Tyre type, front	Size, front	Tyre type, rear	Size, rear	Comment
	Metzeler				
	Roadtec Z8 Interact	120/70 ZR17 M/C (58W) TL	Roadtec Z8 Interact C	190/55 ZR17 M/C (75W)	
K 1600 B, K61		Model code: 0F51			
	Tyre type, front	Size, front	Tyre type, rear	Size, rear	Comment
	ryre type, nont	3126, 110111	Tyre type, rear	312e, 1eai	Comment

K 1600 B, K61 (USA)		Model code: 0F53			
	Roadtec 01 HWM	120/70 ZR17 M/C (58W) TL	Roadtec 01 HWM	190/55 ZR17 M/C (75W)	
	Metzeler				
	T 30F L	120/70 ZR17 M/C (58W)	T 30R L	190/55 ZR17 M/C (75W)	
	BT 022F F	120/70 ZR17 M/C (58W)	BT 021R F	190/55 ZR17 M/C (75W)	

Tyre type, front	Size, front	Tyre type, rear	Size, rear	Comment
Bridgestone				
BT 022F F	120/70 ZR17 M/C (58W)	BT 021R F	190/55 ZR17 M/C (75W)	
T 30F L	120/70 ZR17 M/C (58W)	T 30R L	190/55 ZR17 M/C (75W)	
Metzeler				
Roadtec 01 HWM	120/70 ZR17 M/C (58W) TL	Roadtec 01 HWM	190/55 ZR17 M/C (75W)	

No.	Description
2	if not included in listing on registration document have tyre pair entered by technical inspectorate.
3	if not included in listing on registration document have tyre pair entered by technical inspectorate or keep certificate with the vehicle at all times.
4	The maximum permissible top speed of 160 km/h must be stated where it is clearly noticeable in the rider's field of vision (e.g. sticker).
5	The maximum permissible top speed of 130 km/h must be stated where it is clearly noticeable in the rider's field of vision (e.g. sticker).
6	On tube type rim fit tube.
7	Rear-wheel rim 5.00x17
8	Rear-wheel rim 5.50x17

9	Cast wheels, rims MTH2 3.50x17E and MTH2 4.50x18E
11	Approved for special vehicles only.
12	Tubeless.
13	Not permissible for special vehicles.
15	The maximum permissible top speed of 170 km/h must be stated where it is clearly noticeable in the rider's field of vision (e.g. sticker).
16	Approved only without ABS.
17	Rear-wheel rim 6.00x17
18	Clearance certificate must be obtained from the tyre manufacturer.
19	Spoked wheels, rims MTH2 1.85x21 and MTH2 2.50x17
20	Spoked wheels, rims MTH2 3.50x17 and MTH2 4.00x17

21	Fit the front tyre with tube, because the rim is not suitable for tubeless tyres.
22	Tyre not in production at this time.
23	Rear-wheel rim 2.75x18
24	Rear-wheel rim 3.00x17
25	Approved for cast wheels.
27	Operation permissible only without spray guard fitted (see on-board documentation for instructions on removal and installation).
28	Recommended for OE forged wheel
29	Not for forged wheel OE

30	If the rear wheel tyre size is changed from 190/55 ZR 17 to 200/55 ZR 17 or vice versa, the parameters of the control systems have to be re-coded; BMW Motorrad recommends having this work done by an authorised BMW Motorrad dealer.
31	For tubeless rim only.
32	The maximum permissible top speed of 190 km/h must be stated where it is clearly noticeable in the rider's field of vision (e.g. sticker).
33	National-market version for China
34	National-market version for Brazil
35	Recommended for OE carbon wheel